

Panel Mount, Fixing Nut, 5 x 20 or 6.3 x 32 mm, IP 40



250 VAC · 4 W / 10 A (VDE) · 20 A (UL)

**Beschreibung**

- Quick-connect or solder terminals

Standards

- IEC 60127-6
- UL 512
- CSA C22.2 no. 39

Approvals

- VDE License Number: 134125
- UL File Number: E39328

References

General Product Information

Accessories



WeblinksApprovals: <http://www.schurter.com/approvals>RoHS: <http://www.schurter.com/rohs>**Technical Data**

Shocksafe Category	PC2
Fuse-Link	5 x 20 or 6.3 x 32 mm
Mounting	Panel Mount, Front-Side
Fastening	Fixing Nut
Terminal	Solder or Quick-Connect 4.8 x 0.5 mm
Rated Voltage	250 VAC
Rated Current	10 A (VDE) , 20 A (UL)
Rated Power Acceptance IEC	4 W / 10 A @ Ta 23 °C Admissible power acceptance at higher ambient temperature see derating curves
Degree of Protection	IP 40
Protection Class	Suitable for appliances with protection class I or II acc. to IEC 61140
Admissible Ambient Air Temp.	-40 °C to 85 °C
Climatic Category	40/085/21 acc. to IEC 60068-1
Material: Socket	Thermoplastic, black, UL 94V-0
Material: Terminals	Tin-Plated Copper Alloy
Unit Weight (Socket/Cap)	5.5 g / 3.22 g
Storage Conditions	0 °C to 60 °C, max. 70% r.h.
Product Marking	Type, Voltage Rating, Current Rating, Approvals

Soldering Methods	Iron
Solderability	350 °C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 2
Resistance to Soldering Heat	350 °C / 10 sec acc. to IEC 60068-2-20, Test Tb, method 2
Contact Resistance	< 5 mΩ at 20 mV
Dielectric Strength	> 3 kV between L-N > 4 kV between L/N-PE (50 Hz; 1 min)
Impulse Withstand Voltage	> 4 kV between L-N > 6 kV between L/N-PE
Insulation Resistance	> 10 MΩ between L-N > 100 MΩ between L/N-PE (500 VDC; 1 min)
Overvoltage Category	I - III acc. to IEC 60664-1
Pollution Degree	1 - 3 acc. to IEC 60664-1
Admissible Torque on Fixing Nut	max 1.2 Nm
Panel Thickness s	max 7 mm


Dimensions

Length 46.5 mm




Variant 0031.1693 and 0031.8822


Variant 0031.1694



Variant 0031.1653




Variant 0031.1673



Mounting holes

Derating Curves



Variants

Order Number	Holder	Cap	Fuse-Link	Terminal	Position End-Terminal	Degree of Protection	Colour Cap
0031.1693	●		5 x 20 or 6.3 x 32mm	Quick-Connect 4.8 x 0.5 mm	90° to Fuse Axis	IP 40	
0031.1694	●		5 x 20 or 6.3 x 32mm	Quick-Connect 4.8 x 0.5 mm	Straight to Fuse Axis	IP 40	
0031.8822	●		5 x 20 or 6.3 x 32mm	Solder	90° to Fuse Axis	IP 40	
0031.1653	●		5 x 20 or 6.3 x 32mm	Solder	90° to Fuse Axis	IP 40	
0031.1673	●		5 x 20 or 6.3 x 32mm	Solder	90° to Fuse Axis	IP 40	
0031.1661		Slotted	6.3 x 32mm			IP 40	
0031.1663		Slotted	5 x 20mm			IP 40	
0031.1666		Slotted	6.3 x 32mm			IP 40	Grey

Packaging Unit Bulk (100 pcs.)