


PKD PKE PKC

POLYPROPYLENE INSULATED END SLEEVES

for flexible copper cables



The PK... range of end sleeves is manufactured from tin plated electrolytic copper. Designed and developed to reinforce the fine wire strands, when terminating a cable into a connector block. The PKD series of insulated end sleeves comply with specification DIN 46 228/4.

Recommended crimping tools are shown on pages 84 to 91 and 95

VALSTAR ND#2/PKD

Comprising:

- a selection of end sleeves PKD conductor size 1÷6 sqmm
- tool ND#2

VALSTAR ND#2/PKE

Comprising:

- a selection of end sleeves PKE conductor size 1÷6 sqmm
- tool ND#2

VALSTAR ND#2/PKC

Comprising:

- a selection of end sleeves PKC conductor size 1÷6 sqmm
- tool ND#2

Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	Quantity Box/Bag
		Ø	B	P	L		
0,3÷0,5	PKD 506	2,6	1,4	6,0	12,0	white	10.000/500
	PKD 508	2,6	1,4	8,0	14,0		10.000/500
	PKD 510	2,6	1,4	10,0	16,0		10.000/500
0,75	PKD 7506	2,8	1,6	6,0	12,4	grey	10.000/500
	PKD 7508	2,8	1,6	8,0	14,0		10.000/500
	PKD 7510	2,8	1,6	10,0	16,4		10.000/500
	PKD 7512	2,8	1,6	12,0	18,4		10.000/500
1	PKD 106	3,0	1,8	6,0	12,4	red	10.000/500
	PKD 108	3,0	1,8	8,0	14,0		10.000/500
	PKD 110	3,0	1,8	10,0	16,4		10.000/500
	PKD 112	3,0	1,8	12,0	18,4		10.000/500
1,5	PKD 1508	3,5	2,1	8,0	14,0	black	10.000/500
	PKD 1510	3,5	2,1	10,0	16,4		7.500/500
	PKD 1512	3,5	2,1	12,0	18,4		7.500/500
	PKD 1518	3,5	2,1	18,0	24,4		5.000/500
2,5	PKD 2508	4,2	2,6	8,0	15,0	blue	7.500/500
	PKD 2512	4,2	2,6	12,0	19,0		5.000/500
	PKD 2518	4,2	2,6	18,0	25,0		5.000/500
4	PKD 410	4,8	3,3	10,0	17,0	grey	5.000/200
	PKD 412	4,8	3,3	12,0	19,0		4.000/200
	PKD 418	4,8	3,3	18,0	25,0		3.000/200
6	PKD 612	6,3	4,0	12,0	20,0	yellow	2.500/100
	PKD 618	6,3	4,0	18,0	26,0		2.000/100
10	PKD 1012	7,6	5,0	12,0	21,5	red	1.500/100
	PKD 1018	7,6	5,0	18,0	27,5		1.500/100
	PKD 1612	8,8	6,4	12,0	22,5	blue	1.000/100
16	PKD 1618	8,8	6,4	18,0	28,5		1.000/100
25	PKD 25016	11,2	7,9	16,0	29,0	yellow	500/50
	PKD 25022	11,2	7,9	22,0	35,0		500/50
35	PKD 35016	12,7	8,8	16,0	30,0	red	500/50
	PKD 35025	12,7	8,8	25,0	39,0		400/50
50	PKD 50020	15,0	11,0	20,0	36,0	blue	300/50
	PKD 50025	15,0	11,0	25,0	41,0		300/50

Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	Quantity Box/Bag
		Ø	B	P	L		
0,1÷0,3	PKC 306	1,9	1,1	6,0	10,4	light blue	25.000/500
	PKC 308	1,9	1,1	8,0	12,4		25.000/500
0,3÷0,5	PKC 508	2,6	1,3	8,0	14,0	orange	10.000/500
	PKC 510	2,6	1,3	10,0	16,0		10.000/500
0,75	PKC 7508	2,8	1,6	8,0	14,0	white	10.000/500
	PKC 7512	2,8	1,6	12,0	18,4		10.000/500
1	PKC 108	3,0	1,8	8,0	14,0	yellow	10.000/500
	PKC 112	3,0	1,8	12,0	18,4		10.000/500
1,5	PKC 1508	3,5	2,1	8,0	14,0	red	10.000/500
	PKC 1510	3,5	2,1	10,0	16,4		7.500/500
2,5	PKC 1518	3,5	2,1	18,0	24,4	blue	5.000/500
	*PKC 2508	4,2	2,6	8,0	15,0		7.500/500
4	*PKC 2512	4,2	2,6	12,0	19,0	grey	5.000/500
	*PKC 2518	4,2	2,6	18,0	25,0		5.000/500
6	*PKC 410	4,8	3,3	10,0	17,0	black	5.000/200
	*PKC 412	4,8	3,3	12,0	19,0		4.000/200
10	*PKC 418	4,8	3,3	18,0	25,0	ivory	3.000/200
	PKC 612	5,8	3,9	12,0	20,0		2.500/100
16	PKC 618	5,8	3,9	18,0	26,0	green	2.000/100
	PKC 1012	7,4	4,9	12,0	21,5		1.500/100
25	PKC 1018	7,4	4,9	18,0	27,5	brown	1.500/100
	PKC 1612	8,8	6,2	12,0	22,7		1.000/100
35	PKC 1618	8,8	6,2	18,0	28,6	beige	1.000/100
	PKC 25016	10,0	7,9	16,0	29,0		500/50
50	PKC 25022	10,0	7,9	22,0	35,0	olive	500/50
	PKC 35016	12,0	8,9	16,0	30,0		500/50
	PKC 35025	12,0	8,9	25,0	39,0		400/50
	PKC 50020	13,8	11,0	20,0	36,0		300/50
	PKC 50030	13,8	11,0	30,0	46,0		250/50

Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	Quantity Box/Bag
		Ø	B	P	L		
0,1÷0,3	PKE 308	1,9	1,1	8,0	12,4	yellow	25.000/500
0,3÷0,5	*PKE 508	2,6	1,3	8,0	14,0	white	10.000/500
0,75	PKE 7508	2,8	1,6	8,0	14,0	blue	10.000/500
1	*PKE 108	3,0	1,8	8,0	14,0	red	10.000/500
	*PKE 1508	3,5	2,1	8,0	14,0		10.000/500
1,5	*PKE 1510	3,5	2,1	10,0	16,4	black	7.500/500
	*PKE 1518	3,5	2,1	18,0	24,4		5.000/500
2,5	PKE 2508	4,2	2,6	8,0	15,0	grey	7.500/500
	PKE 2512	4,2	2,6	12,0	19,0		5.000/500
4	PKE 2518	4,2	2,6	18,0	25,0	orange	5.000/500
	PKE 410	4,8	3,3	10,0	17,0		5.000/200
6	PKE 412	4,8	3,3	12,0	19,0	green	4.000/200
	PKE 418	4,8	3,3	18,0	25,0		3.000/200
10	PKE 612	5,8	3,9	12,0	20,0	brown	2.500/100
	PKE 618	5,8	3,9	18,0	26,0		2.000/100
16	PKE 1012	7,4	4,9	12,0	21,5	white	1.500/100
	PKE 1018	7,4	4,9	18,0	27,5		1.500/100
25	PKE 1612	8,8	6,2	12,0	22,7	black	1.000/100
	PKE 1618	8,8	6,2	18,0	28,6		1.000/100
	PKC 25016	10,0	7,9	16,0	29,0		500/50
	PKC 25022	10,0	7,9	22,0	35,0		500/50

Insulated chain end sleeves

Developed for use with production equipment, to give a quick and reliable crimped joint. Conforms to DIN standard 46 228/4.

Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	Quantity Reel
		Ø	B	P	L		
0,3÷0,5	CPKD 508	2,6	1,3	8,0	14,0	white	5.000
0,75	CPKD 7508	2,8	1,5	8,0	14,0	grey	5.000
1	CPKD 108	3,0	1,7	8,0	14,0	red	5.000
1,5	CPKD 1508	3,5	2,0	8,0	14,0	black	5.000
2,5	CPKD 2508	4,2	2,5	8,0	14,0	blue	3.000


*To DIN standard 46 228/4



"TWIN" POLYPROPYLENE INSULATED END SLEEVES

for fine stranded cables

PKT



Conductor Size sqmm	Ref.	Dimensions mm				Insulation Colour	ND#1,ND#2,ND#3 and HNKE 50 Compression Aperture	Quantity Box/Bag
		C	B	P	L			
	PKT 7508	5,2x2,6	2,1	8,0	15,0	grey	1,5	2.500/100
	PKT 7512	5,2x2,6	2,1	12,0	19,0			2.500/100
	PKT 108	5,8x3,2	2,6	8,0	16,0	red	1,5	2.500/100
	PKT 112	5,8x3,2	2,6	12,0	20,0			2.500/100
	PKT 1508	6,5x3,6	2,6	8,0	16,0	black	2,5	2.500/100
	PKT 1512	6,5x3,6	2,6	12,0	20,0			2.500/100
	PKT 2510	7,5x4,3	3,2	9,0	18,0	blue	4	2.500/100
	PKT 2512	7,5x4,3	3,2	12,0	21,0			2.500/100
	PKT 412	9,0x5,2	4,2	12,0	23,0	grey	6	1.500/100
	PKT 614	10,0x7,2	5,3	14,0	26,0	yellow	10	1.000/100
	PKT 1014	13,0x7,2	7,0	14,0	26,0	red	16	500/50
	PKT 1614	18,0x9,5	8,8	14,0	30,0	blue	35	300/50

Type PKT range of end sleeves is manufactured from tin plated electrolytic copper.


Designed to accommodate two cables terminating in the same sleeve.

Recommended crimping tools are shown on pages 84 to 91 and 95

UNINSULATED END SLEEVES

for flexible copper cables

KE



Conductor Size sqmm	Ref.	Dimensions mm			Quantity Box/Bag
		Ø	L	C	
0,5	*KE 506 ST	1,0	6	2,1	50.000/500
	KE 508 ST	1,0	8	2,1	50.000/500
0,75	*KE 7506 ST	1,2	6	2,3	50.000/500
	KE 7508 ST	1,2	8	2,3	50.000/500
1	*KE 106 ST	1,4	6	2,5	25.000/500
	*KE 110 ST	1,4	10	2,5	25.000/500
1,5	*KE 1508 ST	1,8	7	2,8	25.000/500
	*KE 1510 ST	1,8	10	2,8	25.000/500
2,5	*KE 2508 ST	2,3	7	3,4	25.000/500
	*KE 2510 ST	2,3	10	3,4	20.000/500
4	*KE 410 ST	2,8	9	4,0	12.500/500
	*KE 412 ST	2,8	12	4,0	12.500/500
6	*KE 610 ST	3,5	10	4,7	10.000/500
	*KE 612 ST	3,5	12	4,7	7.500/500
10	*KE 616 ST	3,5	15	4,7	5.000/500
	*KE 1016 ST	4,5	15	5,8	4.000/250
16	*KE 1616 ST	5,8	15	7,5	3.000/250
	KE 25012 ST	7,3	12	9,5	2.500/100
25	*KE 25018 ST	7,3	18	9,5	1.500/100
	KE 35012 ST	8,3	12	11,0	1.500/100
35	*KE 35018 ST	8,3	18	11,0	1.000/100

*To DIN standard 46 228/1

KE series end sleeves is manufactured from tin plated electrolytic copper.

Designed and developed for use with flexible cables.

Recommended crimping tools are shown on pages 84 to 91 and 95