

Features

- The Complementary NPN Types are the TIP31 Respectively
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings @ 25°C Unless Otherwise Specified


- Operating Junction Temperature Range: -65°C to +150°C
- Storage Temperature Range: -65°C to +150°C
- Thermal Resistance: 3.125°C/W Junction to Case
- Thermal Resistance: 62.5°C/W Junction to Ambient

Parameter	Symbol	Rating	Unit
Collector-Base Voltage	TIP32	-40	V
	TIP32A	-60	
	TIP32B	-80	
	TIP32C	-100	
Collector-Emitter Voltage	TIP31	-40	V
	TIP31A	-60	
	TIP31B	-80	
	TIP31C	-100	
Emitter-Base Voltage	V_{EBO}	-5	V
Continuous Collector Current	I_C	-3	A
Peak Collector Current	I_{CM}	-5	A
Base Current	I_B	-1	A
Power Dissipation @ $T_C=25^\circ\text{C}$	P_D	40	W
Power Dissipation @ $T_A=25^\circ\text{C}$	P_D	2	W

Note: 1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

PNP Silicon Power Transistors

TO-220



1.BASE
2.COLLECTOR
3.EMITTER

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.560	0.625	14.22	15.88	
B	0.380	0.420	9.65	10.67	
C	0.140	0.190	3.56	4.82	
D	0.020	0.045	0.51	1.14	
F	0.139	0.161	3.53	4.09	Φ
G	0.090	0.110	2.29	2.79	
H	-----	0.250	-----	6.35	
J	0.012	0.025	0.30	0.64	
K	0.500	0.580	12.70	14.73	
L	0.045	0.060	1.14	1.52	
N	0.190	0.210	4.83	5.33	
Q	0.100	0.135	2.54	3.43	
R	0.080	0.115	2.04	2.92	
S	0.045	0.055	1.14	1.39	
T	0.230	0.270	5.84	6.86	
U	-----	0.050	-----	1.27	
V	0.045	-----	1.15	-----	

Electrical Characteristics @ $T_A=25^\circ\text{C}$ Unless Otherwise Specified

Parameter		Symbol	Min	Typ	Max	Units	Conditions
Collector-Emitter Breakdown Voltage	TIP32	$V_{(BR)CEO}$	-40			V	$I_C=-30\text{mA}$, $I_B=0$
	TIP32A		-60				
	TIP32B		-80				
	TIP32C		-100				
Collector Cutoff Current	TIP32	I_{CES}			-200	μA	$V_{CE}=-40\text{V}$, $V_{EB}=0$
	TIP32A				-200	μA	$V_{CE}=-60\text{V}$, $V_{EB}=0$
	TIP32B				-200	μA	$V_{CE}=-80\text{V}$, $V_{EB}=0$
	TIP32C				-200	μA	$V_{CE}=-100\text{V}$, $V_{EB}=0$
Collector Cutoff Current	TIP32	I_{CEO}			-300	μA	$V_{CE}=-30\text{V}$, $I_B=0$
	TIP32A				-300	μA	$V_{CE}=-30\text{V}$, $I_B=0$
	TIP32B				-300	μA	$V_{CE}=-60\text{V}$, $I_B=0$
	TIP32C				-300	μA	$V_{CE}=-60\text{V}$, $I_B=0$
Emitter Cutoff Current		I_{EBO}			-1	mA	$V_{EB}=-5\text{V}$, $I_C=0$
DC Current Gain		$h_{FE(1)}$	25				$V_{CE}=-4\text{V}$, $I_C=-1\text{A}$
		$h_{FE(2)}$	10		50		$V_{CE}=-4\text{V}$, $I_C=-3\text{A}$
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$			-1.2	V	$I_C=-3\text{A}$, $I_B=-0.375\text{A}$
Base-Emitter Voltage		V_{BE}			-1.8	V	$V_{CE}=-4\text{V}$, $I_C=-3\text{A}$
Transition Frequency		f_T	3			MHz	$V_{CE}=-10\text{V}$, $I_C=-500\text{mA}$

Curve Characteristics

Fig. 1 - Static Characteristics




Fig. 2 - DC Current Gain Characteristics




Fig. 3 - Collector-Emitter Saturation Voltage Characteristics




Fig. 4 - Base-Emitter Saturation Voltage Characteristics




Fig. 5 - Base-Emitter Voltage Characteristics





Fig. 6 - Collector Power Derating Curve



Ordering Information

Device	Packing
Part Number-BP	Bulk: 1Kpcs/Box

Note : Adding "-HF" Suffix for Halogen Free, eg. Part Number-BP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp** . and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Micro Commercial Components \(MCC\):](#)

[TIP32C-BP](#)